DECLARATION OF PERFORMANCE N. CPR-IT4/R132 ver. 08/04/2024

1) Unique identification code of the product-type: **POLYLASTIC**

2) Intended uses: **Coatings to be used under ceramic tiles bonded with adhesives (DM-01)**

3) Manufacturer: **POLYGLASS S.P.A Via Giorgio Squinzi, 2 - 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com**

4) System of VVCP: **System 4**
System 3 for water impermeability

5) Harmonized standards: **EN 14891:2012**

Notified bodies: **Elletipi, N. 1308**

6) Performances declared:

Essential characteristics	Performance
Initial tensile adhesion	**> 0,5 N/mm²**
Water impermeability	**No penetration**
Crack bridging capacity:	
- at low temperature (-5 ° C)	**> 0,75 mm**
Durability	
- traction adhesion after thermal aging	**> 0,5 N/mm²**
- traction adhesion after immersion in water	**> 0,5 N/mm²**
- traction adhesion after immersion in lime water	**> 0,5 N/mm²**
- traction adhesion after freeze-thaw cycles	**> 0,5 N/mm²**
Release of dangerous substances	**See SDS**

The performance of the product identified above is in conformity with the set of declared performances.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Ing. P. Ciferni**

In Ponte di Piave 08/04/2024 .....

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that Polyglass makes available on the website along with this current Declaration of Performance.

Version 2:	*Change logo*

POLYLASTIC
CE MARKING
N. CPR-IT4/R132 ver. 08/04/2024

CE 1308	Via Giorgio Squinzi, 2 - 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com

19
CPR-IT4/R132 rev. 08/04/2024
EN 14891
POLYLASTIC
Coatings to be used under ceramic tiles bonded with adhesives (DM-01)

Initial tensile adhesion	> 0,5 N/mm^2
Water impermeability	No penetration
Crack bridging capacity:	
- at low temperature (-5 ° C)	> 0,75 mm
Durability	
- traction adhesion after thermal aging	> 0,5 N/mm^2
- traction adhesion after immersion in water	> 0,5 N/mm^2
- traction adhesion after immersion in lime water	> 0,5 N/mm^2
- traction adhesion after freeze-thaw cycles	> 0,5 N/mm^2
Release of dangerous substances	See SDS

Note:

Polyglass supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values which can be omitted from the CE marking,*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*